UpadIV ME


SERIES PRODUCT SPECIFICATION

UpadIV ME0307 Outdoor Rental LED Display



Product Features

- Stunning Visual Effects – 5000nits, 16bits and 7680Hz
- Sophisticated Touring System – maximum hanging height of 24 meters
- High Transparency—50%
- Curve Range – (Convex) -15°~+15°(Concave)



SPECIFICATION PARAMETERS

Specification		UpadIV ME0307
Cabinet Parameter	Pixel Pitch	3.9-7.8 mm
	LED Type	3-in-1 SMD
	Pixel Density	32,768 pixels/m²
	Module Size	500×125 mm
	Pixels Per Panel	256×128 pixels
	Panel Size with/without Wind-bracing Frame	W1000×H1000×D106/103 mm
	Weight with/without Wind-bracing Frame	25.5/20 kg/panel
	Maintenance	Rear
	Ingress Protection	IP65
	Curve	(Convex) -15°~+15°(Concave)
	Recommended Viewing Distance	≥3.9 m
	Material	Profile Aluminum
	Certification	CE/CB/FCC/ISED/UL
Optical Parameter	Brightness	5,000 nits
	Transparency	50%
	Calibration	Support Brightness and Chroma
	Color Temperature	2,000-9,500K Adjustable
	Viewing Angle	150°/150°
	Contrast Ratio	6000:1
	Gray Scale	16 bit
	LED Life Time	100,000 Hours
Electrical Parameter	Input Power <Max>	510 W/panel
	Input Power <Typical>	170 W/panel
	Input Voltage	100~240 VAC
	Refresh Rate	7,680@60 Hz
	Video Frame Rate	50/60 Hz
	Scan Rate	1/8
Operation Conditions	Operating Temperature/Humidity	-20~+45℃/10~90%RH
	Storage Temperature/Humidity	-20~+55℃/10~60%RH
	Standard Mounting Configuration	Hanging, Stacking

Note:

1. The image of the product above is for illustration only and may differ from the actual product (including but not limited to appearance, color, size, etc.).
2. The parameters are reference values, part of which is obtained under a specific test environment in Unilumin' s internal laboratory, there may be slight differences in actual use due to differences in product batch, configuration, software versions, use conditions, and environmental factors.
3. The power consumption tolerance: ±15%, due to LED batch differences, according to actual situation.